

# Butane

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations  
 Revision Date: 11/12/2025 Date of issue: 10/23/2022

Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Butane

#### 1.2. Intended Use of the Product

**Use of the substance/mixture:** Fuel; Refinery feedstock.

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

Midstream Energy Partners USA, LLC

P.O. Box 430,

Tupman, CA, 93276

661-765-4087

#### 1.4. Emergency Telephone Number

**Emergency Number** : 800-424-9300 Chemtrec - Company Code: 843281

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### Classification (GHS-US)

Simple Asphyxiant

Flam. Gas 1 H220

Liquefied gas H280

Full text of H-phrases: see section 16

#### 2.2. Label Elements

##### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



##### Signal Word (GHS-US)

: Danger

##### Hazard Statements (GHS-US)

: H220 - Extremely flammable gas.  
 H280 - Contains gas under pressure; may explode if heated.  
 - May displace oxygen and cause rapid suffocation.

##### Precautionary Statements (GHS-US)

: P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. - No smoking.  
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
 P381 - Eliminate all ignition sources if safe to do so.  
 P403 - Store in a well-ventilated place.  
 P410+P403 - Protect from sunlight. Store in a well-ventilated place.

#### 2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Contact with gas escaping the container can cause frostbite.

#### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Butane	(CAS No) 106-97-8	> 90	Simple Asphy, H380 Flam. Gas 1, H220 Liquefied gas, H280

# Butane

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Isobutane	(CAS No) 75-28-5	< 6	Simple Asphy, H380 Flam. Gas 1, H220 Liquefied gas, H280
Ethylene	(CAS No) 74-85-1	< 2	Simple Asphy, H380 Flam. Gas 1, H220 Compressed gas, H280 STOT SE 3, H336
Propene	(CAS No) 115-07-1	< 2	Simple Asphy, H380 Flam. Gas 1, H220 Compressed gas, H280
Pentane	(CAS No) 109-66-0	< 2	Flam. Liq. 1, H224 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Propane	(CAS No) 74-98-6	< 1.5	Simple Asphy, H380 Flam. Gas 1, H220 Compressed gas, H280

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.

**First-aid Measures After Inhalation:** Obtain medical attention if breathing difficulty persists. First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a comfortable position for breathing.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**First-aid Measures After Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** May cause frostbite on contact with the liquid. Asphyxia by lack of oxygen: risk of death.

**Symptoms/Injuries After Inhalation:** In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

**Symptoms/Injuries After Skin Contact:** Contact with gas/liquid escaping the container can cause frostbite and freeze burns.

**Symptoms/Injuries After Eye Contact:** Contact with gas/liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage.

**Symptoms/Injuries After Ingestion:** Not considered a potential route of exposure, but contact with gas/liquid escaping the container can cause freeze burns and frostbite.

**Chronic Symptoms:** None expected under normal conditions of use.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Do not extinguish burning gas if flow cannot be shut off immediately. Extinguish secondary FIRES with appropriate materials.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising from the Substance or Mixture

**Fire Hazard:** Extremely flammable gas.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture. Container may explode in heat of fire.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

# Butane

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Other Information:** Use water spray to disperse vapors. Do not allow run-off from firefighting to enter drains or water courses.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Eliminate every possible source of ignition. Do not breathe gas.

#### 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Responders

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Evacuate unnecessary personnel, isolate, and ventilate area. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Stop leak, if possible, without risk. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering.

### 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable. Ruptured cylinders may rocket. Do not pressurize, cut, or weld containers. Asphyxiating gas at high concentrations.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Do not breathe gas. Employ good maintenance practices to prevent leaks. Use good process control measures to prevent releases.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep in fireproof place. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling.

**Incompatible Products:** Strong acids, strong bases, strong oxidizers.

**Special Rules on Packaging:** Ethyl mercaptan might, under certain conditions (when oxygen, water, iron oxide or other oxidizers are present in containers and piping) react with oxidizers which diminish or eliminate entirely its distinct smell, thereby reducing or eliminating the ability of a person to detect a leak. The passage of odorized propane through soil because of an underground leak will also diminish or eliminate entirely the smell of odorized propane. If you suspect a leak, use a combustible gas indicator or similar device to check for gas leaks.

### 7.3. Specific End Use(s)

Fuel; Refinery feedstock.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), or OSHA (PEL).

Propane (74-98-6)		
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>

# Butane

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	1000 ppm
<b>USA IDLH</b>	US IDLH (ppm)	2100 ppm (10% LEL)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	1000 ppm
<b>Isobutane (75-28-5)</b>		
<b>USA ACGIH</b>	ACGIH STEL (ppm)	1000 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	800 ppm
<b>Butane (106-97-8)</b>		
<b>USA ACGIH</b>	ACGIH STEL (ppm)	1000 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	800 ppm
<b>Ethylene (74-85-1)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	200 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>Propene (115-07-1)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	500 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>Pentane (109-66-0)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	1000 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	120 ppm
<b>USA NIOSH</b>	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (ceiling) (ppm)	610 ppm
<b>USA IDLH</b>	US IDLH (ppm)	1500 ppm (10% LEL)
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2950 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	1000 ppm

## 8.2. Exposure Controls

### Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Use explosion-proof equipment. Oxygen detectors should be used when asphyxiating gases may be released.

### Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



### Materials for Protective Clothing

: Wear fire/flammable resistant/retardant clothing.

### Hand Protection

: Wear protective gloves.

### Eye Protection

: Chemical safety goggles.

### Skin and Body Protection

: Wear suitable protective clothing.

### Respiratory Protection

: Use a NIOSH-approved self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

### Thermal Hazard Protection

: Wear thermally resistant protective clothing.

### Other Information

: When using it, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

#### Physical State

: Gas

#### Appearance

: Colorless

#### Odor

: Faint, disagreeable odor

#### Odor Threshold

: 5000 ppm

# Butane

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>pH</b>	: No data available
<b>Evaporation Rate</b>	: Gas at normal ambient conditions
<b>Melting Point</b>	: No data available
<b>Freezing Point</b>	: -217 °F
<b>Boiling Point</b>	: 31 °F
<b>Flash Point</b>	: - 76 °F (TCC)
<b>Auto-ignition Temperature</b>	: 760 °F
<b>Decomposition Temperature</b>	: No data available
<b>Flammability (solid, gas)</b>	: Extremely flammable gas
<b>Lower Flammable Limit</b>	: 1.6%
<b>Upper Flammable Limit</b>	: 8.4%
<b>Vapor Pressure</b>	: 50 - 75
<b>Relative Vapor Density at 20 °C</b>	: 2 (Air=1)
<b>Specific Gravity</b>	: 0.5842 @ 60 °F
<b>Solubility</b>	: Water: Slight
<b>Partition Coefficient: N-Octanol/Water</b>	: No data available
<b>Viscosity</b>	: No data available
<b>Molecular Weight</b>	: 58.1
<b>Explosive Properties</b>	: Contains gas under pressure; may explode if heated.

### 9.2. Other Information

**Gas Group** : Liquefied gas

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Contains gas under pressure; may explode if heated.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, open flames, sources of ignition and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Normal combustion produces carbon dioxide; incomplete combustion can produce carbon monoxide.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information On Toxicological Effects

**Acute Toxicity:** Not classified

<b>Propane (74-98-6)</b>	
<b>LC50 Inhalation Rat</b>	658 mg/l/4h
<b>Isobutane (75-28-5)</b>	
<b>LC50 Inhalation Rat</b>	658 mg/l/4h
<b>LC50 Inhalation Rat</b>	11000 ppm
<b>Butane (106-97-8)</b>	
<b>LC50 Inhalation Rat</b>	30957 mg/m <sup>3</sup> (Exposure time: 4 h)
<b>Propene (115-07-1)</b>	
<b>LC50 Inhalation Rat</b>	658 mg/l/4h
<b>Pentane (109-66-0)</b>	
<b>LD50 Dermal Rabbit</b>	3000 mg/kg
<b>LC50 Inhalation Rat</b>	364 g/m <sup>3</sup> (Exposure time: 4 h)

**Skin Corrosion/Irritation:** Not classified

**Serious Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

# Butane

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Ethylene (74-85-1)</b>	
<b>IARC group</b>	3
<b>Propene (115-07-1)</b>	
<b>IARC group</b>	3

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

**Symptoms/Injuries After Skin Contact:** Contact with gas/liquid escaping the container can cause frostbite and freeze burns.

**Symptoms/Injuries After Eye Contact:** Contact with gas/liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage.

**Symptoms/Injuries After Ingestion:** Not considered a potential route of exposure, but contact with gas/liquid escaping the container can cause freeze burns and frostbite.

**Chronic Symptoms:** None expected under normal conditions of use.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

<b>Ethylene (74-85-1)</b>	
<b>ErC50 (algae)</b>	72 mg/l
<b>Pentane (109-66-0)</b>	
<b>LC50 Fish 1</b>	9.87 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
<b>EC50 Daphnia 1</b>	9.74 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>LC 50 Fish 2</b>	11.59 mg/l (Exposure time: 96 h - Species: Pimephales promelas)

### 12.2. Persistence and Degradability

<b>Butane</b>	
<b>Persistence and Degradability</b>	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative Potential

<b>Butane</b>	
<b>Bioaccumulative Potential</b>	Not established.
<b>Propane (74-98-6)</b>	
<b>Log Pow</b>	2.3
<b>Isobutane (75-28-5)</b>	
<b>BCF fish 1</b>	1.57 - 1.97
<b>Log Pow</b>	2.88 (at 20 °C)
<b>Butane (106-97-8)</b>	
<b>Log Pow</b>	2.89
<b>Ethylene (74-85-1)</b>	
<b>BCF fish 1</b>	4 - 4.6
<b>Log Pow</b>	0.053
<b>Propene (115-07-1)</b>	
<b>Log Pow</b>	<= 2.8
<b>Pentane (109-66-0)</b>	
<b>Log Pow</b>	3.39

**12.4. Mobility in Soil** No additional information available

### 12.5. Other Adverse Effects

**Other Information** : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

# Butane

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions. Handle empty containers with care because residual vapors are flammable. Empty gas cylinders should be returned to the vendor for recycling or refilling. Do not puncture or incinerate container.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. In Accordance with DOT

Proper Shipping Name(s) : BUTANE  
 PETROLEUM GASES, LIQUEFIED

Hazard Class : 2.1

Identification Number : UN1011  
 UN1075

Label Codes : 2.1

ERG Number : 115



### 14.2. In Accordance with IMDG

Proper Shipping Name(s) : BUTANE  
 PETROLEUM GASES, LIQUEFIED

Hazard Class : 2

Division : 2.1

Identification Number : UN1011  
 UN1075

Label Codes : 2.1

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U



### 14.3. In Accordance with IATA

Proper Shipping Name(s) : BUTANE  
 PETROLEUM GASES, LIQUEFIED

Identification Number : UN1011  
 UN1075

Hazard Class : 2

Label Codes : 2.1

Division : 2.1

ERG Code (IATA) : 10L



## SECTION 15: REGULATORY INFORMATION

### 15.1 US Federal Regulations

<b>Butane</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Fire hazard Sudden release of pressure hazard Immediate (acute) health hazard
<b>Propane (74-98-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Isobutane (75-28-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Butane (106-97-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Ethylene (74-85-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Propene (115-07-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Pentane (109-66-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

# Butane

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

--	--

# Butane

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2 US State Regulations

<b>Propane (74-98-6)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Isobutane (75-28-5)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Butane (106-97-8)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Ethylene (74-85-1)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Propene (115-07-1)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Pentane (109-66-0)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

<b>Revision Date</b>	: 11/12/2025
<b>Other Information</b>	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### GHS Full Text Phrases:

Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration Hazard Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 1	Flammable liquids Category 1
Liquefied gas	Gases under pressure Liquefied gas
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H220	Extremely flammable gas
H224	Extremely flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H336	May cause drowsiness or dizziness
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*